### **HDS 9/17-4 C CLASSIC**

Three-phase hot water high-pressure cleaner with water-cooled electric motor, ecolefficiency mode, integrated tanks, EASY!Force trigger gun, continuous pressure/water flow regulation and so much more.















#### Order no.

1.174-905.0

- Economical eco!efficiency mode
- Intuitive single-button selector switchFour-pole water-cooled electric motor

Technical data		
EAN code		4054278168630
Supply voltage	Ph/V/Hz	3 / 400 / 50
Flow rate	l/h	290 - 900
Working pressure	bar / MPa	30 - 170 / 3 - 17
Temperature (for supply 12 °C)	°C	max. 80
Connected load	kW	6.5
Consumption of heating oil or gas at full load	kg/h	5.6
Power cable	m	5
Fuel tank	1	15
Weight (with accessories)	kg	121
Weight incl. packaging	kg	129.8
Dimensions (L × W × H)	mm	1060 × 650 × 920

Users must receive training on this device.

Equipment		
Spray gun		EASY!Force Advanced
High-pressure hose	m	10 / ID 8, 315 bar
Spray lance	mm	1040
Power nozzle		
Soft Damping System (SDS)		
Pressure switch-off		
Integrated fuel and cleaning agent tank		
Included in the scane of comply		

HDS 9/17-4 C Classic, 1.174-905.0, 2024-01-19









#### Efficiency

- ecolefficiency mode efficient and environmentally friendly, even when used for prolonged periods.
- Reduces fuel consumption and CO2 emissions by 20%.

#### Ease of use

- Intuitive operation thanks to the large single-button selector switch.
- Large tank opening with filling chute.
- Convenient system care bottle can be changed from the outside.

#### Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cable and high-pressure hose.
- Integrated lance holder for transport.






























TRICGER CUNS  TRICGER CUNS  TOTAL CONTROL OF TRICE Advanced  \$1					
EASY Force Advanced			Order no.	Description	
EASYIForce Advanced  1 4.118-005.0 Effortless, not energy-sapping: the EASYIForce high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the objection to zero.  2 4.111-050.0 For retrofitting Karcher high-pressure cleaners with existing high-pressure hose: EASYIForce conversion kit 1 - from high-pressure hose conversion kit 2 - from machine  3 4.111-051.0 Developed for retrofitting existing high-pressure cleaners from Karcher: EASYIForce conversion kit 2 - from machine  4 4.111-052.0 Compatible with existing high-pressure gun, spray lance: EASYIForce conversion kit 3, incl. EASYIForce conversion kit 3 - high-pressure hose and necessary adapters.  EASYIForce conversion kit 3 - high-pressure deaners.  EASYIForce trigger gun and all necessary adapters for upgrading your high-pressure cleaner.  Servo Control, 750 l/h - 1100 l/h  5 4.118-008.0 Water quantity and pressure regulated directly from the hand spray gun.  SPRAY LANCES  PROVIDED TO THE PROVIDED T	TRIGGER GUNS				
high-pressure jet to reduce the holding force for the operator to zero.  EASYIForce conversion kit 1 - from high-pressure lose high-pressure hose high-pressure hose leaving from machine leaving from	Spray guns				
high-pressure hose conversion kit 1 with EASY[Force high-pressure gun, spray lance and all adapters through to the nozzle.  EASY[Force conversion kit 2 - from machine 2 4 1.11-05.0 Developed for retrofitting existing high-pressure cleaners from Karcher: EASY[Force conversion kit 2 with EASY[Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. 2 with EASY[Force conversion kit 3 - high-pressure hose and spray lance: EASY[Force conversion kit 3, incl. gun 2 with EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force conversion kit 3, incl. gun 3 with expressure hose and spray lance: EASY[Force conversion kit 3, incl. gun 3 with EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force conversion kit 3, incl. gun 4 with EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force conversion kit 3, incl. gun 4 with EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force conversion kit 3, incl. gun 4 with EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. EASY[Force only a pun 4 with expressure lance (manual coupling) with ergonomic handle for ease of use and protection, Rotatable 360° under pressure.  EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure lance (manual coupling) with ergonomic handle for ease of use and protection, Rotatable 360° under pressure.  EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure lance (manual coupling) with ergonomic handle for ease of use and protection, Rotatable 360° under pressure.  EASY[Force trigger gun and all necessary adapters for upgrading your high-pressure pungrading your high-pressure during the pressure.  EASY[Force trigger gun and all necessary adapters for upgrading your	EASY!Force Advanced	1	4.118-005.0		
EASY!Force conversion kit 3 - high-pressure gun and leading the sasy!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.  EASY!Force conversion kit 3 - high-pressure gun and all necessary adapters for upgrading your high-pressure cleaner.  Servo control, 750 l/h - 1100 l/h  5		2	4.111-050.0	conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the	
Servo Control, 750 l/h - 1100 l/h	EASY!Force conversion kit 2 - from machine	3	4.111-051.0		
Servo Control, 750 I/h - 1100 I/h  5   4.118-008.0   Water quantity and pressure regulated directly from the hand spray gun.   □  SPRAY LANCES  Rotating spray lances  Spray lance, 1050 mm, rotatable   6   4.112-000.0   1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   □  LED nozzle light   7   2.680-002.0   Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.  Spray lance, 250 mm, rotatable   8   4.112-027.0   Spray lance, 250 mm, rotatable, ergonomic   □  Spray lance, 400 mm, rotatable   9   4.112-024.0   Spray lance, 400 mm, rotatable, ergonomic   □  Spray lance, 600 mm, rotatable   10   4.112-007.0   600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 440 mm, rotatable   11   4.112-006.0   850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable   12   4.112-018.0   1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable   13   4.112-021.0   2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.		4	4.111-052.0		
SPRAY LANCES   Rotating spray lances   Spray lance, 1050 mm, rotatable   6   4.112-000.0   1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   1.2	Servo control			\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	
Rotating spray lances  Spray lance, 1050 mm, rotatable  6 4.112-000.0 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  LED nozzle light  7 2.680-002.0 Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.  Spray lance, 250 mm, rotatable  8 4.112-027.0 Spray lance, 250 mm, rotatable, ergonomic  Spray lance, 400 mm, rotatable  9 4.112-024.0 Spray lance, 400 mm, rotatable, ergonomic  Spray lance, 600 mm, rotatable  10 4.112-007.0 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  11 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Servo Control, 750 l/h - 1100 l/h	5	4.118-008.0	Water quantity and pressure regulated directly from the hand spray gun.	
Spray lance, 1050 mm, rotatable  6   4.112-000.0   1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  LED nozzle light  7   2.680-002.0   Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.  Spray lance, 250 mm, rotatable  8   4.112-027.0   Spray lance, 250 mm, rotatable, ergonomic  Spray lance, 400 mm, rotatable  9   4.112-024.0   Spray lance, 400 mm, rotatable, ergonomic  Spray lance, 600 mm, rotatable  10   4.112-007.0   600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11   4.112-006.0   850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12   4.112-018.0   1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13   4.112-021.0   2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	SPRAY LANCES				
protection. Rotatable 360° under pressure.  LED nozzle light  7 2.680-002.0 Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.  Spray lance, 250 mm, rotatable  8 4.112-027.0 Spray lance, 250 mm, rotatable, ergonomic  Spray lance, 400 mm, rotatable  9 4.112-024.0 Spray lance, 400 mm, rotatable, ergonomic  Spray lance, 600 mm, rotatable  10 4.112-007.0 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11 4.112-006.0 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Rotating spray lances				
gun. Better view in unfavourable lighting conditions for up to 5 working hours.  Spray lance, 250 mm, rotatable  8 4.112-027.0 Spray lance, 250 mm, rotatable, ergonomic  Spray lance, 400 mm, rotatable  9 4.112-024.0 Spray lance, 400 mm, rotatable, ergonomic  Spray lance, 600 mm, rotatable  10 4.112-007.0 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11 4.112-006.0 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Spray lance, 1050 mm, rotatable	6	4.112-000.0		
Spray lance, 400 mm, rotatable  9 4.112-024.0 Spray lance, 400 mm, rotatable, ergonomic  Spray lance, 600 mm, rotatable  10 4.112-007.0 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11 4.112-006.0 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	LED nozzle light	7	2.680-002.0		
Spray lance, 600 mm, rotatable  10 4.112-007.0 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11 4.112-006.0 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
protection. Rotatable 360° under pressure.  Spray lance, 840 mm, rotatable  11 4.112-006.0  850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0  1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0  2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
protection. Rotatable 360° under pressure.  Spray lance, 1550 mm, rotatable  12 4.112-018.0 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Spray lance, 600 mm, rotatable	10	4.112-007.0		
protection. Rotatable 360° under pressure.  Spray lance, 2050 mm, rotatable  13 4.112-021.0 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	Spray lance, 840 mm, rotatable	11	4.112-006.0		
protection. Rotatable 360° under pressure.	Spray lance, 1550 mm, rotatable	12	4.112-018.0		
Spray lance extender, 1000 mm 14 4.112-048.0 Spray lance extension with EASY!Lock connection. Length 1000 mm.	Spray lance, 2050 mm, rotatable	13	4.112-021.0		
	Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\square$  Available accessories.























		1		
		Order no.	Description	
SPRAY LANCES				
Double lance				
Double lance, 960 mm	15	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance			.94	
Spray lance for toilets and rain gutters	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from $20^\circ$ to $140^\circ$ , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle			/,0	
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°			CX	
Power nozzle , 054	22	2.113-011.0	Flat jet nozzle for large area performance and stubborn dirt.	
HP nozzle spray angle 0°			7	
Power nozzle 0°, 050	23	2.113-034.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				
Power nozzle 15°, 055	24	2.113-047.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 40°				_
Power nozzle 40°, 055	25	2.113-055.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, DN 6, 250 bar, 2 × EASY!Lock	26	6.110-035.0	10 m long high-pressure hose (DN 6) equipped with EASY!Lock manual screw fitting on both sides. Suitable up to 250 bar and with ANTI!Twist.	-
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	27	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 10 m, DN 6, 250 bar, 2 × EASY!Lock	28	6.110-034.0	10 m long high-pressure hose with EASY!Lock manual screw fitting on both sides. Nominal size DN 6, suitable up to 250 bar.	

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\hfill\Box$  Available accessories.



















		Order no.	Description	
HIGH-PRESSURE HOSES				Ť
Standard with unions on both sides				
High-pressure hose, 10 m, DN 6, 300 bar, 2 × EASY!Lock	29	6.110-056.0	High-pressure hose (DN 6) equipped with ANT!!Twist and the new EASY!Lock manual screw fitting on both sides. For pressures up to 300 bar. 10 m long.	I
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	30	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANT!!Twist and 10 m long.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	31	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	32	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	33	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	34	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar. 15 m long high-pressure hose (DN 10).	-:
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	35	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	36	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	37	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	1
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	38	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	39	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	40	6.110-024.0	1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure.	
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, $1 \times EASY!Lock / 1 \times M22 \times 1.5$	41	6.110-069.0	1.5 m long high-pressure hose (DN 8) suitable for up to 400 bar pressure with double steel core. Connections: M $22 \times 1.5$ , as well as the comfortable and quick EASY!Lock manual screw fitting.	
High-pressure hose Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	42	6.110-038.0	Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure.	

 $<sup>\ \</sup>square$  Available accessories.

## ACCESSORIES FOR HDS 9/17-4 C CLASSIC 1.174-905.0

























				-
		Order no.	Description	L
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	43	6.110-023.0	Robust high-pressure hose with double steel core, ANTI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	44	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
High-pressure hose Longlife, 15 m, DN 8, 400 bar, $2 \times EASY!Lock$	45	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	
Food industry version with unions on both side	es			4
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	46	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	47	6.110-052.0	Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections.	
Longlife food design with screw connections at	t both	ends		Ī
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	48	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	49	6.110-054.0	Durable high-pressure hose with double steel reinforcement and blue, non-marking and animal fat resistant outer covering. 20 m long with EASY!Lock hand screw connections.	Г
Special hoses				4
High-pressure hose curved, 1.5 m, DN 8, 400 bar, $1 \times EASY!Lock / 1 \times M22 \times 1.5$	50	6.110-068.0	For connection to hose reels: high-pressure hose, with M $22 \times 1.5$ connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure.	[
WEED CONTROL				4
WR 50	51	2.114-013.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	[
WR 20	52	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	[
WR 100	53	2.114-015.0	Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	[
WR 10	54	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	[
QUICK CONNECT				Į
Quick coupling	55	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M $22 \times 1.5$ internal thread.	[
Male coupling	56	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 × 1.5 external	[

### **ACCESSORIES FOR HDS 9/17-4 C CLASSIC**

### 1.174-905.0























		Order no.	Description	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	57	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	[
OTHER HP ACCESSORIES				Ť
Jet gun	58	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
FLUE PIPE				
Flue gas adapter	59 60		Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	[
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large			/ V7 / V	
Dirt blaster, large, 055/060	61	4.114-036.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzland bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e [
MULTIPLE-JET NOZZLES				Ť
Angled vario nozzle 0-90°	. (			
Angled Vario nozzle, 055	62	4.113-008.0	Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.	f [
STEAM JET NOZZLE / NOZZLE PROTECTOR / RO	DLLOV	ER NOZZLE		
Steam jet nozzles				
Steam jet nozzle 50°	63	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	64	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	1
PIPE CLEANING				Ť
Pipe cleaning hose, ID 6		/(		
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	65	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	66	6.110-008.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	[
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	67	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle		1		Ť
Pipe cleaning dirt blaster D21/060	68	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Pipe cleaning dirt blaster D30/060	69	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.	Ī
Pipe cleaning nozzle 120	70	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	[

### **ACCESSORIES FOR HDS 9/17-4 C CLASSIC** 1.174-905.0



























-		100	
	d	k	
84	- 4		

	1			-
		Order no.	Description	
PIPE CLEANING				
Pipe cleaning nozzle				
Pipe cleaning nozzle	71	5.763-015.0		
	72	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	73	5.763-021.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	74	6.415-440.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Hose fastening attachment kit	75	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Dirt trap attachment kit	76	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
FR 30 Me surface cleaner				
Hard Surface Cleaner FR 30 Me	77	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50			V / - X '	
Surface Cleaner FR 50 Me	78	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	g
Machine-specific nozzle kits for FR				
Nozzle kit for FR, 850 l/h - 1100 l/h	79	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FRV			V .	
Nozzle kit for FRV, 080	80	2.642-982.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
FRV 30 Me surface cleaner				_
FRV 30 Me Surface Cleaner	81	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Extension hose FRV 30 Me and FRV 50 Me	82	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FOAM SYSTEMS				Т
Cup foam lance				
Cup foam lance Advanced 3, 900 l/h - 2500 l/h	83	4.112-065.0	Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher.	
Cup foam lance DUO Advanced 3, 900 l/h - 2500 l/h	84	4.112-069.0	DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank.	

## ACCESSORIES FOR HDS 9/17-4 C CLASSIC 1.174-905.0



























		Ouden ne	Province	
FOAM SYSTEMS		Order no.	Description	_
Cup foam lance				_
Cup foam lance Basic 3, 900 l/h - 2500 l/h	85	4.112-055.0	High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality.	
1-litre cleaning agent container for cup foam lance basic	86	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	
1-litre cleaning agent container for cup foam lance advanced	87	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Kit		I.		_
Inno Foam Set with detergent injector	88	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For	
Inno Foam Set	89	2.112-008.0	use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				$^{+}$
Easy Foam Set with RM injector	90	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for	
Easy Foam Set	91	2.112-011.0	connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set			Y/0\(\)	Ť
Nozzle kit 090 for Inno / Easy Set 700-1,000 l/h	92	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.	
Foam nozzle mounting kit				
Foam nozzle attachment kit	93	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
Cleaning agent injector			X	
Cleaning agent injector for high and low pressure (without nozzles)	94	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Cleaning agent injector for high pressure (without nozzle)	95	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with order no. 4.63	7-033	3.0		
Nozzle kit 750-1000 l/h	96	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 4.637-032.0				
Nozzle insert up to 1,100 l/h - high pressure	97	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low pressure	98	4.769-001.0	For low pressure with machines up to 1.100 l/h	Г





























	Order no.	Description	
99	4.111-021.0	Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
	•		
100	4.111-022.0	For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) – $1 \times$ M $22 \times 1.5/1 \times$ M $18 \times 1.5$ .	
101	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
102	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	ot 🗆
	•	. 1777	
103	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
104	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
105	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
106	4.111-032.0	Adapter 4 to connect the new gun with the old swivel hose	
107	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
108	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
109	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
110	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
111	4.111-037.0	Adapter 9 to connect the new hose with the new hose	
112	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
	100 101 102 103 104 105 106 107 108 109 110	99 4.111-021.0  100 4.111-022.0  101 4.111-024.0  102 4.111-038.0  103 4.111-030.0  104 4.111-030.0  105 4.111-031.0  106 4.111-033.0  107 4.111-034.0  108 4.111-035.0  110 4.111-036.0  111 4.111-037.0	99 4.111-021.0 Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection  100 4.111-022.0 For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - 1 × M 22 × 1.5/1 × M 18 × 1.5.  101 4.111-024.0 Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.  102 4.111-038.0 For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.  103 4.111-029.0 Adapter 1 to connect the old hose with the new hose 104 4.111-030.0 Adapter 2 to connect the old device with the new hose and the old gun with the new hose 105 4.111-031.0 Adapter 3 to connect the old gun with the new spray lance and new servo regulator 106 4.111-032.0 Adapter 4 to connect the new gun with the old swivel hose 107 4.111-033.0 Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance 108 4.111-034.0 Adapter 6 to connect the new device with the old hose and the old hose with the new gun 109 4.111-035.0 Adapter 7 to connect the new device with the new nozzle 110 4.111-036.0 Adapter 8 to connect the new spray lance with the new nozzle 111 4.111-037.0 Adapter 9 to connect the new hose with the new hose 112 4.111-046.0 Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M

 $<sup>\ \</sup>square$  Available accessories.



## ACCESSORIES FOR HDS 9/17-4 C CLASSIC 1.174-905.0



























		Order no.	Description	
HOSE REELS				
Manual hose reel attachment kit				
Hose reel attachment kit for HDS compact class, 20 m	113	2.110-010.0	Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hoses (with a connection hose for the machine high-pressure outlet). Rotatable under pressure with connection for male coupling.	
Automatic, self-winding hose reels for wall mo	untin	g		
Automatic plastic hose reel incl. high-pressure hose, 15 m	114	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	
Automatic hose reel, powder-coated steel / plastic, 20 m	115	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	116	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	117	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	118	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	119	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	120	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	121	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	122	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Automatic, self-winding hose reel attachment	kit	7 /		
Attachment kit automatic hose reel HDS C	123	2.110-012.0	Complete automatic hose reel attachment kit for HDS compact class. Simple installation and all unit functions are accessible. Offers maximum convenience when winding and unwinding the HP hose. Contains: Automatic hose reel, HP hose and all connection parts.	
Attachment kit automatic hose reel holder HDS	124	2.110-013.0	Holder includes connection material for installing an automatic hose reel to machines from the HDS compact class.	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	125	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	126	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	

























		Order no.	Description			
FACADE AND SOLAR PANEL CLEANING						
Brushes						
Roller brush 500 soft	127	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.			
Roller brush 500 medium	128	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.			
Roller brush 500 hard	129	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.			
Brush hard	130	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.			
Brush medium	131	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.			
Brush soft	132	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Karcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.			
iSolar 800 Advanced	133	6.368-094.0	iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of $700-1,000 \text{ l/h}$ . With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	) 🗆		
iSolar 400 Advanced	134	6.368-092.0	iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.			
Telescopic lances						
TL low pressure adapter	135	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.			
Telescopic lance TL 7 F	136	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical guick-release fasteners for simple retraction and extension.			
Telescopic lance TL 7 H	137	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	. 🗆		
Telescopic lance TL 10 H	138	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.			
Telescopic lance TL 10 C	139	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.			
Telescopic lance TL 14 C	140	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.			

<sup>☐</sup> Available accessories.

### ACCESSORIES FOR HDS 9/17-4 C CLASSIC

#### 1.174-905.0





















		1		
		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Telescopic lances				
TL high pressure adapter	141	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
Water softening	,		94 1/10	
WS 50	142	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS 100	143	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS Regenerator	144	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening unit: WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s $\square$
Hoses			A V7/ W	
iSolar HP hose 7	145	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 10	146	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
iSolar HP hose 14	147	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters			7.0	
iSolar fall protection	148	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	149	4.115-000.0	Paint, rust and scale removal made easy: Kārcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	150	4.115-006.0	Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation	
Boron carbide nozzle				
Boron carbide nozzle, for machines up to 1,000 l/h	151	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Barrel cleaner BC 14/12	152	2.112-020.0	The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres.	
HKF 50 spray head, brass				
HKF 50 M spray head	153	3.631-039.0	Constant rotational speed and lightweight design: The compact interior cleaning head for cleaning vats and tanks with openings of 50 mm or wider.	
90	154	3.631-058.0	Compact interior cleaning head for cleaning containers with openings of 50 millimetres or wider. The device stands out from the crowd with its constant rotational speed and lightweight design.	
			I .	





















		Order no.	Description	
DRUM AND TANK CLEANING				
Nozzle kit for spray head HKF 50 (3.631-009.0	7 3.63	31-039.0)		
Nozzle 045 for 2-nozzle operation HKF 50	155	6.415-446.0	Nozzle for dual-nozzle operation	
High-pressure full jet nozzle 090 for interior cleaning heads	156	6.415-447.0	High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of $0^{\circ}$ , made of hardened stainless steel and with 1/8-inch thread.	
Double grip for precise control of spray head	157	2.863-036.0	Double handle. Precise control of the spray head	
1/8" screw plug for interior cleaning heads	158	5.411-061.0	Screw plug for high-pressure interior cleaning heads with 1/8-inch thread.	
ADD ON KITS				
Flame monitoring attachment kit				
Flame monitoring attachment kit for HDS Compact Class	159	2.642-711.0	A light sensor monitors the burner flame. The fuel supply is shut off if the flame goes out.	
WATER CONNECTION				Ť
Geka coupling		. 1		
Geka connector with hose barb, R 1/2"	160	6.388-461.0	with hose liner	
Geka connector with hose barb, R 3/4"	161	6.388-455.0		
Geka connector with hose barb, R 1"	162	6.388-465.0	with hose barb	
Geka connector with internal thread, R 1"	163	6.388-458.0	with female thread	
Suction filter				
Water suction filter	164	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μm mesh, R 3/4" and R 1" connection, without non-return valve	n 🗆
Suction filter with check valve	165	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter		7/	10	
Universal water fine filter, 25 µm	166	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	
Water fine filter, with adapter	167	4.730-102.0	Fine-mesh water filter, 125 $\mu$ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	r,
Water fine filter, 100 µm, R 1"	168	2.638-270.0	Fine-mesh water filter, $100 \mu m$ , max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protect the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$ . Connector 1".	ıs 🗆

<sup>☐</sup> Available accessories.

## ACCESSORIES FOR HDS 9/17-4 C CLASSIC 1.174-905.0







4.113-003.0





Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to  $60^{\circ}$ C, M  $18 \times 1.5$  (replaceable brush insert).

			<b>( ) /</b> ( )
		Order no.	Description
WATER CONNECTION			
Water supply hose			
Water supply hose	169	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C
	170	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up
WASHING BRUSHES			
Push-on washing brush			
Push-on wash brush	171	4.113-001.0	For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection
Rotating washing brush			
Rotating wash brush for < 1000 l/h machines, nylon bristles	172	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to $60^{\circ}$ C. (M $18 \times 1.5$ , replaceable brush insert).

<sup>☐</sup> Available accessories.

natural bristles

Rotating wash brush for < 800 l/h machines,

