

# ART. 5732 sim. DIN 603 EN ISO 8677

Vite a testa tonda larga con quadro sottotesta, senza dado

*Cup head square neck bolt*

Disponibile con filetto parziale o totale

A4

A2

*Available with full or partial thread*

dk	12,45/13,55	15,45/16,55	19,35/20,65	23,35/24,65	29,35/30,65	37,20/38,80
f	2,90/4,10	3,40/4,60	4,40/5,60	5,40/6,60	7,25/8,75	11,10/12,90
k	2,70/3,30	3,12/3,88	4,12/4,88	4,62/5,38	6,05/6,95	8,05/8,95
l ≤ 125 mm	16	18	22	26	30	38
b 125 mm < l ≤ 200 mm	22	24	28	32	36	44
l > 200 mm	--	--	41	45	49	57
v	4,52/5,48	5,52/6,48	7,42/8,58	9,42/10,58	11,30/12,70	15,30/16,70
l/d	M5	M6	M8	M10	M12	M16
12	Tf/Ft	Tf/Ft				
16	Tf/Ft	Tf/Ft	Tf/Ft			
20	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft		
25	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	
30	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	
35	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft	Tf/Ft	
40	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft	
45	Tf/Ft	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft	
50	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft
55	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	
60	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft
65	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	Tf/Ft	
70	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft
75	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	Tf/Ft	Tf/Ft	
80	Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	
90		Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	
100		Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	
110			Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	
120		Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	
130			Tf/Ft - Pf/Pt	Tf/Ft - Pf/Pt	Tf/Ft	
140			Tf/Ft	Tf/Ft	Tf/Ft	
150			Tf/Ft	Tf/Ft - Pf/Pt	Tf/Ft	
160			Tf/Ft	Tf/Ft	Tf/Ft	
180				Tf/Ft	Tf/Ft	
200				Tf/Ft	Tf/Ft	
220				Tf/Ft	Tf/Ft	

Tf/Ft = Totale filetto / Full Thread

Pf/Pt = Parziale Filetto / Partial Thread

last edit 16/12/2019

DRAWING N. 1023