



Compressed air grease gun-DL

M 10 x 1-GBDR-MU

Item number:	18 071
EAN:	4103810180712
Discount group:	D

Technical data

Grease gun connection, pressure-side:	M 10 x 1
Filling nipple:	M 10 x 1
Capacity (cm ³):	500
Refilling options:	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Pressure ratio:	50:1
Grease supply into the grease gun head:	spring operated
Diameter of grease piston (mm):	6
Grease pump piston actuation:	single-stroke grease supply
Delivery rate/stroke (cm ³):	0,8
Recommended air pressure (bar):	6
Min. air pressure (bar):	2
Max. air pressure (bar):	8
Compressed air connection:	hose nozzle, 6 mm, for hose, DN 6 (20 132)
Pump pressure at 8 bar air pressure (bar):	400
Burst pressure system (bar):	850
Burst pressure grease gun head (bar):	1200
Operation of push rod:	with L-design handle
Cover:	loose
Wall thickness of grease gun tube (mm):	1,0
Lacquering:	silver
Weight (kg):	1,84

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Angled spout, M 10 x 1, 150 mm (12 635)
- Coupler, 4 jaws, M 10 x 1 (12 631)
- Sales package, with Bar code

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm):	402 x 171 x 84
Weight including package (kg):	1,99
Packing unit:	1,0

