



AIR COMPRESSORS AND PNEUMATIC TOOLS



3. BELT DRIVEN SINGLE-STAGE AND TWO-STAGE COMPRESSORS

BD 220/100-2M

BXCM0105E



- Pump with cast-iron cylinder for long-lasting durability.
- Sturdy belt guard protects all moving parts.
- Large wheels and convenient grip handle make transport easy.

| | |
|-------------------|-----------------------|
| Code | BMFC404BND315 |
| Pump | MK102N |
| Tank | 100 l |
| Power | 2 Hp / 1,5 kW |
| Cylinder | 2 |
| Max Pressure | 10 bar / 145 PSI |
| Lubricated | YES |
| RPM | 1375 |
| Air displac. | 220 l/min. / 7,77 CFM |
| Voltage/Frequence | 230 Volt / 50 Hz |
| Weight | 61,5 kg / 135,6 lb |
| Dimensions | 950x390x770 |
| Ean code | 8016738763775 |



- Also available the following models:

BD 220/50-2M

BXCM0101E

| | |
|-------------------|-----------------------|
| Code | BMDC404BND313 |
| Pump | MK102N |
| Tank | 50 l |
| Power | 2 Hp / 1,5 kW |
| Cylinder | 2 |
| Max Pressure | 10 bar / 145 PSI |
| Lubricated | YES |
| RPM | 1375 |
| Air displac. | 220 l/min. / 7,77 CFM |
| Voltage/Frequence | 230 Volt / 50 Hz |
| Weight | 50,5 kg / 111,3 lb |
| Dimensions | 770x340x670 |
| Ean code | 8016738763751 |

BD 320/50-3M

BXCM0111E

| | |
|-------------------|-----------------------|
| Code | BMDC504BND314 |
| Pump | MK102 |
| Tank | 50 l |
| Power | 3 Hp / 2,2 kW |
| Cylinder | 2 |
| Max Pressure | 10 bar / 145 PSI |
| Lubricated | YES |
| RPM | 1250 |
| Air displac. | 320 l/min. / 11,3 CFM |
| Voltage/Frequence | 230 Volt / 50 Hz |
| Weight | 53,5 kg / 118 lb |
| Dimensions | 770x340x670 |
| Ean code | 8016738763768 |

BD 320/100-3M

BXCM0115E

| | |
|-------------------|-----------------------|
| Code | BMFC504BND316 |
| Pump | MK102 |
| Tank | 100 l |
| Power | 3 Hp / 2,2 kW |
| Cylinder | 2 |
| Max Pressure | 10 bar / 145 PSI |
| Lubricated | YES |
| RPM | 1250 |
| Air displac. | 320 l/min. / 11,3 CFM |
| Voltage/Frequence | 230 Volt / 50 Hz |
| Weight | 64,5 kg / 142,2 lb |
| Dimensions | 950x390x770 |
| Ean code | 8016738763782 |